



XENIO-AC200

Sleek & Modern Biometric Security

Smart biometric fingerprint reader built to fit even the slimmest of door panels.

Features



World's #1 Fingerprint Technology

Extra large finger capture area
#1 fingerprint algorithm in
minex iii fbi-piv certified.



5MP Camera

Records a snapshot of the user
at the time of verification.



Flexible APIs

The SekureID Cloud and Xenio APIs
provide methods to manage,
control, and monitor Xenio Smart
Biometric & RFID devices.



Real Time Communication

Designed with today's connected world in mind (IoT "internet of things"). Our communication technology leverages seamless real time data transfer from our devices to third party systems and vice versa.



Dual Frequency Card Reader

The Xenio-AC200 offers dynamic dual frequency support of multiple credential technologies including iCLASS Seos, iClass SE, Standard iCLASS, HID Prox, Standard Prox EM, NFC, Felica MiFARE Classic, and Mifare DESfire EV1.



Power Over Ethernet

Using the existing Local Area Network (LAN) for both power and data eliminates the need for any additional power supply or electrical wiring.

XENIO-AC200



Specifications

COMMUNICATION INTERFACE

PoE (Power Over Ethernet)
Wi-Fi
Bluetooth Smart 4.0
1 Programmable Universal Relay
RS485 (COM)
Wiegand Output
2 TTL Input
1 TTL Output

WHAT'S INCLUDED IN THE BOX

One Xenio-AC200
Xenio Instruction Guide
Wall Mount
Security Screw
Wall Anchors
Wall Mount Screw

POWER

Power: DC 12 Volts
Current (Operational): 1.5A

BIOMETRICS

Fingerprint Technology: Optical Imaging
Image resolution: 500DPI
Scanning area: 17.4 mm x 13mm
Identification Methods: 1:1 or 1:N
User Capacity: 1000 / 10,000 Optional
Fingerprint capacity: 10,000 / 100,000 Optional
Standards: ANSI-378, ISO1974 Certified
with NIST Minex-III, PIV, FBI WSQ and
most industry biometric standards
and interoperability

AUTHENTICATION METHODS

Fingerprint
Smart Card
Mobile

SMART CARD TECHNOLOGY

Standard Reader: 125Khz EM Prox
Optional Dual Frequency Reader:
Frequencies: 125kHz and 13.56 MHz
Supported credential types: HID Prox
EM Prox iClass SE/SR/Seos/
Elite Mifare 1K, 4K, Classic
Certified US Government FIPS 210 PIV II

MEMORY & PROCESSOR

QUAD Core
ARM A9 Cortex 1.6 Ghz
4GB Flash Memory
1GB RAM

DIMENSIONS

Height: 6 inches
Width: 2.75 inches
Deep: 2.50 inches